

SYSTEM 2000 liitosjärjestelmä


| Tilausno | Malli |
|----------|---|
| 0400 | Laippaliitin PE- ja PVC-putkille, vetoa kestävä |



| Laippa DN | Putken Ø mm | D | k | b | L | E | Puttit kpl | Kierr. ig | Paino ig |
|-----------|-------------|-----|-----|----|-----|-----|------------|-----------|----------|
| 50 | 63 | 165 | 125 | 19 | 90 | 80 | 4 | M 16 | 3,6 |
| 65 | 63 | 185 | 145 | 19 | 90 | 80 | 4 | M 16 | 4,3 |
| 65 | 75 | 185 | 145 | 19 | 92 | 82 | 4 | M 16 | 4,3 |
| 80 | 75 | 200 | 160 | 19 | 92 | 82 | 8 | M 16 | 5,0 |
| 80 | 90 | 200 | 160 | 19 | 95 | 85 | 8 | M 16 | 5,5 |
| 100 | 90 | 220 | 180 | 19 | 95 | 85 | 8 | M 16 | 6,8 |
| 100 | 110 | 220 | 180 | 19 | 95 | 85 | 8 | M 16 | 6,2 |
| 100 | 125 | 220 | 180 | 19 | 97 | 87 | 8 | M 16 | 7,0 |
| 125 | 110 | 250 | 210 | 19 | 95 | 85 | 8 | M 16 | 7,8 |
| 125 | 125 | 250 | 210 | 19 | 97 | 87 | 8 | M 16 | 8,2 |
| 125 | 140 | 250 | 210 | 19 | 103 | 93 | 8 | M 16 | 8,5 |
| 150 | 140 | 285 | 240 | 19 | 103 | 93 | 8 | M 16 | 11,3 |
| 150 | 160 | 285 | 240 | 19 | 115 | 105 | 8 | M 20 | 10,5 |
| 150 | 180 | 285 | 240 | 19 | 125 | 115 | 8 | M 20 | 11,8 |
| 200 | 200 | 340 | 295 | 20 | 135 | 125 | 8 | M 20 | 18,0 |
| 200 | 225 | 340 | 295 | 20 | 138 | 128 | 8 | M 20 | 16,0 |
| 250 | 250 | 400 | 350 | 22 | 155 | 145 | 12 | M 20 | 22,0 |
| 250 | 280 | 400 | 350 | 22 | 158 | 148 | 12 | M 20 | 29,0 |
| 300 | 315 | 455 | 400 | 25 | 184 | 174 | 12 | M 20 | 44,0 |
| 300 | 355 | 455 | 400 | 25 | 277 | 237 | 12 | M 20 | |
| 400 | 400 | 565 | 515 | 25 | 242 | 230 | 16 | M 24 | |
| 400 | 450 | 565 | 515 | 25 | 302 | 260 | 16 | M 24 | |
| 500 | 500 | | | | | | | | |
| 600 | 630 | | | | | | | | |


Tarkennat mitat kysyttäessä.

| Tilausno | Malli |
|----------|--|
| 0430 | Jatkoliitin PE- ja PVC-putkille, vetoa kestävä |



| Putken ø mm | L | t | B | Paino kg |
|-------------|-----|-----|-----|----------|
| 63 | 171 | 80 | 124 | 3,2 |
| 75 | 175 | 82 | 138 | 4,0 |
| 90 | 181 | 85 | 152 | 5,4 |
| 110 | 181 | 85 | 172 | 6,4 |
| 125 | 185 | 87 | 193 | 7,8 |
| 140 | 197 | 93 | 210 | 9,0 |
| 160 | 221 | 105 | 236 | 12,0 |
| 180 | 241 | 113 | 258 | 14,5 |
| 200 | 261 | 125 | 284 | 21,5 |
| 225 | 265 | 128 | 314 | 26,0 |
| 250 | 300 | 145 | 347 | 33,0 |
| 280 | 306 | 148 | 376 | 38,5 |
| 315 | 358 | 174 | 422 | 58,5 |

| Tilausno | Malli |
|----------|--|
| 8075 | Päättekappale 2" kierteellä PE- ja PVC-putkille, vetoa kestävä |



| Putken ø mm | L | t | B | Paino kg |
|-------------|-----|-----|-----|----------|
| 63 | 106 | 80 | 124 | 2,7 |
| 75 | 138 | 82 | 138 | 3,2 |
| 90 | 141 | 85 | 152 | 4,5 |
| 110 | 159 | 85 | 172 | 5,8 |
| 125 | 162 | 87 | 193 | 6,1 |
| 140 | 169 | 93 | 210 | 7,4 |
| 160 | 180 | 105 | 236 | 8,6 |
| 180 | 192 | 113 | 258 | 11,7 |
| 200 | 203 | 125 | 284 | 14,5 |
| 225 | 207 | 128 | 314 | 16,5 |
| 250 | 225 | 145 | 347 | 20,5 |
| 280 | 228 | 148 | 376 | 25,0 |
| 315 | 254 | 174 | 422 | 33,5 |